



# DSL-X25 SERIES

---

## LED MINI FLASHING LAMP



### PRODUCT BENEFITS

---

- Available in Blue, Red and Amber emitted light
- Designed with high level Electromagnetic Compatibility (EMC) specifications
- Compact and lightweight design
- Asynchronous and Synchronous patterns
- Multivoltage 10-30V
- IP69K

# FUNCTIONS LAYOUT



# TECHNICAL SPECIFICATIONS

## TECHNICAL DATA

Variants	Series DSL-X25.05	Series DSL-X25.06	Series DSL-X25.08	
Operating Voltage	10 V - 30 V			
Reverse Polarity Protection	Yes			
Light Function	LED Warning Light			
Emitted Color	Amber	Red	Blue	
Consumption	6.3 W	6.2 W	9 W	
Temperature Range	- 40°C to + 65°C			
Type of Mounting	Screw Mounting			
Material	Lens	PC		
	Housing	ADC12		
Type of Protection	IP69K			
Approvals	ECE	R65	R65	R65
		XA1	XR1	XB1
	EMC	00	00	00
Flashing Patterns	R10-06			
	10			
Type of Connection	The products are equipped with either synchronous and/or asynchronous functions			
Type of Connection	500mm Cable			

## CODES OVERVIEW

Variants Ref. No.	Amber	Red	Blue	Synch	Synch & Asynch
DSL-X25S.05	•			•	
DSL-X25S.06		•		•	
DSL-X25S.08			•	•	
DSL-X25.05	•				•
DSL-X25.06		•			•
DSL-X25.08			•		•

## DIMENSIONAL DRAWING

